

FEATURES

- **Straight stream to fog**
- **Corrosion resistant**
- **Extremely light weight**
- **Easy to maintain and clean**

Application

Ideal to use in connection with portable monitors due to their very low weight, remarkable strengths and adjustable discharge pattern.

Recommended Foam Concentrates

The following foam concentrates can be used in combination with Freja:

- AFFF 1%, 3% or 6%
- AFFF ARC* 3x6
- AFFF ARC* 3x3

* not on polar solvents.

Operation

The Freja nozzles are fitted with a 2½" female thread. The ideal operating pressure is 8 bar at the nozzle inlet. By turning the outside part of the nozzle, the discharge pattern can be adjusted from straight stream to fog. After using foam solution, clean it with water.



Freja nozzles are specially designed for Balder monitors or any other monitor with 2½" water outlet. The nozzles are suitable for water and foam solutions. They are manufactured in a plastic composite with similar strength to aluminium.

The discharge pattern is adjustable from fog to straight stream. Standard nominal flow rates for the nozzle are measured at 8 bar.

Technical data

| | |
|----------------------|-------------------|
| Flow rate | 500 lpm |
| Nominal pressure | 8 bar |
| Inlet | 2½" BSP FM thread |
| Material | Plastic composite |
| Length, fog/straight | 155/185 mm |
| Weight | 0.9 kg |
| Part no. | 20-4000-00 |

Throw range with water at 8 bar

