



Dimensions in mm

### CONSTRUCTION FEATURES

Body and flanges material: carbon steel

Rupture disc material: glass

Detachable calibrated orifice material: stainless steel AISI 316

Finish: red epoxy paint (RAL 3000)

### OPTIONAL

Body material: stainless steel (AISI 304 / AISI 316)

Flanges material: stainless steel (AISI 304 / AISI 316)

Hot dip galvanized

MODEL	ØA	ØB	H (mm)	C (mm)	D (mm)	WORKING PRESSURE	FLOW RATE at 5 bar	FOAM PRODUCTION <sup>(1) (2)</sup> at 5 bar	WEIGHT
TYR 2	2"	3"	895	200	500	3 - 12 bar	200 l/min	1500 l/min	30 kg
TYR 4	2"	4"	895	200	500	3 - 12 bar	400 l/min	3000 l/min	32 kg
TYR 8	3"	6"	1.015	300	600	3 - 12 bar	800 l/min	6000 l/min	58 kg
TYR 15	4"	8"	1.086	300	645	3 - 12 bar	1500 l/min	11000 l/min	102,5 kg
TYR 20	4"	8"/10"	1.372	400	855	3 - 12 bar	2000 l/min	14000 l/min	143/150 kg

The original Nordic god of war and the patron god of justice, the precursor of Odin. At the time of the Vikings, Tyr had to make way for Odin, who became the god of war himself. Tyr was by then regarded as Odin's son (or possibly of the giant Hymir). He is the boldest of the gods, who inspires courage and heroism in battle. Tyr is represented as a man with one hand, because his right hand was bitten off by the gigantic wolf Fenrir (in old-Norse, the wrist was called 'wolf-joint'). His attribute is a spear; the symbol of justice, as well as a weapon.

At the day of Ragnarok, Tyr will kill the hound Garm, the guardian of the hell, but will die from the wounds inflicted by the animal. In later mythology, "Tyr" became to mean "god".