



GFGV.EX6015 Foam Liquid Concentrates

[Page Bottom](#)

Foam Liquid Concentrates

[See General Information for Foam Liquid Concentrates](#)

DAFO FOMTEC AB

EX6015

PO BOX 683
SE-135 26 TYRESO, SWEDEN

Fomtec FP 3% UL, nominal 3 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec FP 6% UL, nominal 6 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec ARC 3X3UL, nominal 3 percent Alcohol resistant Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbons and polar fuels only at 3 percent.

Fomtec AFFF 3% Ultra, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 6% Ultra, nominal 6 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 3% S, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec ARC 3X3 S, nominal 3 percent Alcohol resistant Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbons and polar fuels only at 3 percent.

Fomtec AFFF 1% ULTRA LT, nominal 1 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 3% ULTRA LT, nominal 3 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 6% ULTRA LT, nominal 6 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Foam concentrates for use with the following equipment:

Fomtec AFFF 3% Ultra, 3 PERCENT

PROPORTIONERS-PORTABLE IN-LINE INDUCTORS

Viking Corp, Model FE-60, 1-1/2 in. size, set at 3, inlet pressure of 167 psi with 42 mm and 20 m length of hose between inductor and Viking Corp, Model A-60 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Viking Corp, Model A-60	1-1/2	65

Fomtec AFFF 6% Ultra, 6 PERCENT

PROPORTIONERS-PORTABLE IN-LINE INDUCTORS

Viking Corp, Model FE-60, 1-1/2 in. size, set at 6, inlet pressure of 174 psi with 42 mm dia and 20m length of hose between inductor and Viking Corp, Model A-60 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Viking Corp, Model A-60	1-1/2	50

Fomtec FP 3% UL,3 percent

PROPORTIONERS-PORTABLE IN-LINE INDUCTORS

Viking Corp., Model FE-90, 1-1/2 in. size with 50 ft of 1-1/2 in. hose between inductor and National Foam Inc., Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
National Foam Inc.	1-1/2	58
Model JS-10, -10B		

Fomtec FP 6% UL, 6 percent

PROPORTIONERS-PORTABLE IN-LINE INDUCTORS

Viking Corp., Model FE-90, 1-1/2 in. size with 50 ft of 1-1/2 in. hose between inductor and National Foam Inc., Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
National Foam Inc.	1-1/2	58
Model JS-10, -10B		

Fomtec ARC 3X3UL, 3 percent

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

National Foam Inc., Model HLP-9M, 1-1/2 in. size, set at 3 inlet pressure 200 psi with 50 ft of 1 1/2 in. hose between inductor and National Foam, Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
National Foam Inc., Model JS-10	1-1/2	94

PROPORTIONERS - BLADDER TANKS WITH CONTROLLERS

Chemguard Inc. bladder tanks with the following controllers:

Description	Controller Size, in.	Orifice Size, in.	Flow, gpm	Percent Proportioning
Chemguard Inc.	4	0.455	405	3

FIXED FOAM DISCHARGE OUTLETS

Description	Fuel	Orifice Diameter, in.	Inlet Pressure, psi
Chemguard Inc., Model FC 4.0	Alc	1.485	100

Where:

Fuel	Minimum Application Rate, gpm/ft ²
Alc (Alcohols)	0.14

FOMTEC AFFF 3% S, 3%

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi

Viking Model, FE 90 P/N 09178	1-1/2	0.208(5.28 mm)	145	73
-------------------------------	-------	----------------	-----	----

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Viking Corp, SIN VK100, K-Factor 5.6 (1/2 in.)			
Hydrocarbons	Upright	0.16	7.0
Viking Corp, SIN VK102, K-Factor 5.6 (1/2 in.)			
Hydrocarbons	Pendant	0.16	7.0
Viking Corp, SIN VK200, K-Factor 8.0 (17/32 in.)			
Hydrocarbons	Upright	0.22	7.0
Viking Corp, SIN VK202, K-Factor 8.0 (17/32 in.)			
Hydrocarbons	Pendant	0.22	7.0

FOMTEC ARC 3x3 S, 3%

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam In.	Inlet Pressure psi	Back Pressure psi
Viking Model, FE 90 P/N F09176	1-1/2	0.245(6.22 mm)	200	80

SPRINKLERS

Fuel	Style	Min Application Rate GPM/Sq Ft	Min Inlet Pressure psi
Viking Corp, SIN VK100, K-Factor 5.6 (1/2 in.)			
Hydrocarbons	Upright	0.16	7.0
Alcohols	Upright	0.22	14.5
Ketones	Upright	0.29	24.0
Viking Corp, SIN VK102, K-Factor 5.6 (1/2 in.)			
Hydrocarbons	Pendant	0.16	7.0
Alcohols	Pendant	0.26	19.0
Ketones	Pendant	0.29	24.0
Viking Corp, SIN VK200, K-Factor 8.0 (17/32 in.)			
Hydrocarbons	Upright	0.22	7.0
Alcohols	Upright	0.29	12.0
Ketones	Upright	0.32	15.0
Viking Corp, SIN VK202, K-Factor 8.0 (17/32 in.)			
Hydrocarbons	Pendant	0.22	7.0
Alcohols	Pendant	0.29	12.0
Ketones	Pendant	0.32	15.0

FOMTEC AFFF 1% ULTRA LT, 1 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Viking Corp., Model FE-90, 1-1/2 in. size, with 0.098" orifice, with 100 ft of 1-1/2 in. hose between inductor and National Foam Inc., Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi

National Foam Inc., Model JS-10	1-1/2	50
---------------------------------	-------	----

FOMTEC AFFF 3% ULTRA LT, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Viking Corp., Model FE-90, 1-1/2 in. size, with 0.207" orifice, with 100 ft of 1-1/2 in. hose between inductor and National Foam Inc., Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
National Foam Inc., Model JS-10	1-1/2	50

FOMTEC AFFF 6% ULTRA LT, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Viking Corp., Model FE-90, 1-1/2 in. size, with 0.310" orifice, with 100 ft of 1-1/2 in. hose between inductor and National Foam Inc., Model JS-10 nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
National Foam Inc., Model JS-10	1-1/2	50

Last Updated on 2010-03-08

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

