

## Description

Fomtec Forrex Ultra is a specially selected blend of high activity hydrocarbon surfactants, solvents and stabilisers for use on class A fuel fires. Fomtec Forrex Ultra does not contain any hazardous substances and does not require any special labelling when transported.

## Application

Fomtec Forrex Ultra provides excellent extinguishments of class A fires by providing deep penetration of the water into the burning material. At low concentrations it is also highly effective as a Wetting Agent. Fomtec Forrex Ultra can be used with both aspirating and non-aspirating discharge devices. It is compatible with all dry chemical powders.

Fomtec Forrex Ultra can be used in:

- Fire extinguishers
- Foams systems

## Environment

**Fomtec Forrex Ultra is non-hazardous, biodegradable substance totally free from Fluorinated surfactants. As for all foams it should be handled according to the local regulations when used.**

## Typical Performance

Fomtec Forrex Ultra has been designed to be applied as a Wetting Agent as well as a Class A fire extinguishing agent and can be effective if proportioned from 0.1% to 3.0% according to requirements.

## Technical data

Appearance	Clear amber Liquid
Specific gravity @ 20.0°C approx.	1.02 +/- 0.01 g/ml
pH	6.5 – 8.5
Freezing protection	-5° C

## Storage/Shelf Life

Stored in original unbroken packaging or correctly filled in appropriate fire extinguisher or closed from storage tank the product will have a long shelf life. The recommended storage temperature range of Fomtec Forrex Ultra is from -5°C to 50°C. Shelf life of at least 5 years will be found in temperate climates.

## Packaging

We supply Fomtec Forrex Ultra in 25 litre, 200 litre drums and 1000 litre containers or in bulk.