# *LX 800*
## *BRANCHPIPE*



### *FEATURES*

- ***Long throw range***
- ***Good foam quality due to special nozzle***

## Application

- Fire brigades
- Petrochemical plants
- Tank farms
- Loading areas
- Chemical plants

## Recommended Foam Concentrates

- Fluoroprotein 3% or 6%
- Protein 3% or 6%
- FFFP 3% or 6%
- AR-FFFP 3x6 or 3x3
- AFFF 1%, 3% or 6%
- AR-AFFF 3x6 or 3x3
- Multi purpose foam

## Operation

The branchpipe should be connected to the hose-line. To start foam application, open the ball valve. It is also necessary to flush the branch-pipe with clear water after every use.

## Options

The LX 800 could be delivered with the following options:

- Storz couplings
- BS-couplings

**The LX 800 foam branchpipe produces low expansion foam of high quality. The quality is generated by the optimal air inlet nozzle. The advantage of low expansion is the long throw range and the excellent cooling effect.**

## Technical data

| | |
|---|---|
| **Nominal water flow** | **800 lpm** |
| **Operating pressure** | **5 bar** |
| **Expansion rate approx** | **15** |
| **Quantity of foam/min** | **Approx. 12 $m^3$** |
| **External coupling thread** | **2” BSP M** |
| **Throw range** | **36 meters** |
| **Material** | **Stainless steel** |
| **Length** | **890 mm** |
| **Width** | **126 mm** |
| **Height** | **126 mm** |
| **Weight** | **6,1 kg** |
| **Part no.** | **20-1100-50** |