



CERTIFIED COPY

CERTIFICATE OF FIRE APPROVAL

This is to certify that

The product detailed below will be accepted for compliance with the applicable Lloyd's Register Rules and Regulations and with the International Convention for the Safety of Life at Sea, (SOLAS), 1974, as amended, for use on ships and offshore installations classed with Lloyd's Register, and for use on ships and offshore installations when authorised by contracting governments to issue the relevant certificates, licences, permits etc.

Manufacturer	Dafo Fomtec AB
Address	P.O. Box 683 135 26 Tyresö Sweden
Type	DRY CHEMICAL POWDER
Description	Fire Extinguishing Dry Powder for B and C Class Fires – Types: "Renex BCE Standard and Renex BC Plus"
Specified Standard	EN 615 and EN 3 as applicable

The attached Design Appraisal Document forms part of this certificate.

This certificate remains valid unless cancelled or revoked, provided the conditions in the attached Design Appraisal Document are complied with and the equipment remains satisfactory in service.

Date of issue	10 April 2008	Expiry date	9 April 2013
---------------	---------------	-------------	--------------

Certificate No.	SAS F080065
-----------------	-------------

Signed	
--------	---

Sheet No	1 of 2
----------	--------

Name	M. Farrier Surveyor to Lloyd's Register EMEA A Member of the Lloyd's Register Group
------	---

Note:

This certificate is not valid for equipment, the design or manufacture of which has been varied or modified from the specimen tested. The manufacturer should notify Lloyd's Register of any modification or changes to the equipment in order to obtain a valid Certificate.

"Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract."

DESIGN APPRAISAL DOCUMENT

Date 10 April 2008	Quote this reference on all future communications LDSS/PAS/FITA/MF/SA
-----------------------	--

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No. SAS F080065

This Design Appraisal Document forms part of the Certificate.

APPROVAL DOCUMENTATION

Lloyd's Register (Liverpool) Witness Certificates Nos: MCH9902010/5A dated 19 March 1999 and MCH9902010/2B dated 11 April 2001

CONDITIONS OF CERTIFICATION

1. Suitable for Class B and C fires.
2. Renex BC class dry powders are based on calcium carbonate and sodium bicarbonate or potassium sulphate and treated with water insoluble flow promoting additives. The chemical composition of the dry powders are as stated in the table below:

Chemical composition / Properties	Renex BCE Standard	Renex BC Plus
Dry powder density (g/l)	1.05	1.0
Sodium bicarbonate (%)	90	-
Calcium carbonate (%)	10±2	70
Potassium sulphate (%)	-	21
Water insoluble flow additives (%)	>1.0	>2.0

3. Production items are to be manufactured in accordance with a quality control system which shall be maintained to ensure that items are of the same standard as the approved prototype.

PLACE OF PRODUCTION

Dafo Fomtec AB
P.O. Box 683
135 26 Tyresö
Sweden



Martin Farrier
Lead Specialist
Product Approval Services
London Design Support Services
Lloyd's Register EMEA

Supplementary Type Approval Terms and Conditions

This certificate and Design Appraisal Document relates to type approval, it certifies that the prototype(s) of the product(s) referred to herein has/have been found to meet the applicable design criteria for the use specified herein, it does not mean or imply approval for any other use, nor approval of any products designed or manufactured otherwise than in strict conformity with the said prototype(s).