

Description

Fomtec AFFF 3% -45 is an aqueous film forming foam concentrate (AFFF) with very low freezing point (-45°C) to be used in arctic climates.

The foam forms an aqueous film that rapidly cuts off the oxygen supply and thus knocks down the fire. The expanded foam from which the film is drained forms a stable blanket that suppresses the release of flammable vapours and cools down the fuel surface extinguishing the fire and preventing re-ignition.

The low surface tension of the water foam concentrate solution enables the aqueous film, although heavier than the burning liquid, to float on top of the liquid surface.

Fomtec AFFF 3% -45 should be used at 3% proportioned solution (3 part concentrate in 97 parts of water) in fresh or seawater. It may also be stored as a premix solution in fresh water.

Application

Fomtec AFFF 3% -45 is intended for use on class B hydrocarbon fuel fires such as oil, diesel and aviation fuels. It can be used with both aspirating and non-aspirating discharge devices.

Fomtec AFFF 3% -45 is especially suited whenever rapid fire knock-down is essential. It is compatible with all dry chemical powders and can be used in powder/foam twin agent systems.

Fire Performance & Foaming

The foaming properties are depending on equipment used and other variables such as water and ambient temperatures. Foaming index no less than 7:1 (normally 8:1), 25% drainage time 3.0 minutes (normally 3.5).

Proportioning

Fomtec AFFF 3% -45 can easily be proportioned at the correct dilution using conventional equipment such as:

- Inline inductors
- Balanced pressure, variable flow proportioning systems
- Bladder tanks
- Around the pump proportioning systems
- Water turbine driven foam proportioners
- Self inducing branch pipes and nozzles

The equipment should be designed to the foam type.

Compatibility

Contact one of the Fomtec sales team with questions.

Technical data

Appearance	Clear amber liquid
Specific gravity at 20°C	1,025 +/- 0.01 g/ml
Viscosity at 20°C	≤ 20 mPas
pH	6,5 – 8,5
Freezing point	-45°C
Recommended storage temperature	-45 – 55°C
Suspended sediment (v/v)	Less than 0,2%
Surface tension	≤ 20,0 mN/m

Environmental impact

Fomtec AFFF 3% -45 is formulated using raw materials specially selected for their fire performance and their environmental profile. Fomtec AFFF 3% -45 is biodegradable. The handling of spills of concentrate or foam solution should however be undertaken according to local regulations. Normally sewage systems can dispose foam solution based on this type of foam concentrate, but local sewage operators should be consulted in this respect. This product contains NO PFOS or PFOA. Fomtec AFFF 3% -45 is formulated with the latest fluorine technology and uses only “All-C6 fluorinated” compounds.

Full details will be found in the Material Safety Datasheet (MSDS).

Storage / Shelf life

Stored in original unbroken packaging the product will have a long shelf life. The recommended storage temperature range of Fomtec AFFF 3% -45 is from -45°C to 55°C. Freezing and thawing will have no impact on the performance.

Synthetic foam concentrates should only be stored in stainless steel or plastic containers. Since electromagnetic corrosion can occur at joints between different metals when they are in contact with foam concentrate, only one type of metal should be used for pipelines, fittings, pumps, and tanks employed in the storage of foam concentrates. We recommend following our guidelines for storage and handling ensuring favourable storage conditions.

Packaging

We supply this product in 25 litre cans and 200 litre drums. We can also ship in 1000 litre containers or in bulk.

Litres per piece	Packaging	Part no
25 litres	Can	10-3006-41
200 litres	Drum	10-3006-42
1000 litres	Container	10-3006-44
Bulk	Special request	

International Approvals

IMO MSC.1 Circ. 1312
MED Wheelmarked