

CERTIFICATE OF COMPLIANCE

Certificate Number EX6015
Report Reference EX6015-20051207
Date 2021-June-22

Issued to: DAFO FOMTEC AB
Po Box 683
Tyreso135 26 SE

**This is to certify that
representative samples of**

FOAM LIQUID CONCENTRATES
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 162, Foam Equipment and Liquid Concentrates
ULC-S564, Categories 1 and 2 Foam Liquid Concentrates

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number EX6015
Report Reference EX6015-20051207
Date 2021-June-22

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Foam liquid concentrates as follows:

Fomtec FP 3% UL, nominal 3 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec FP 6% UL, nominal 6 percent, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec ARC 3X3UL, nominal 3 percent Alcohol resistant Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbons and polar fuels only at 3 percent.

Fomtec AFFF 3% S, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec ARC 3X3 S, nominal 3 percent Alcohol resistant Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbons and polar fuels only at 3 percent.

Fomtec AFFF 1% ULTRA LT, nominal 1 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 3% ULTRA LT, nominal 3 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 6% ULTRA LT, nominal 6 percent Aqueous Film Forming Foam, +0°F (-18 °C) minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 3% ULTRA, nominal 3 percent Aqueous Film Forming Foam, +35°F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec AFFF 6% ULTRA, nominal 6 percent Aqueous Film Forming Foam, +35°F minimum storage and use temperature. Hydrocarbon fuels only.


FOMTEC FFFP-ARC 3x3 NV Avalanche, nominal 3 percent Alcohol Resistant Film Forming Fluoroprotein Foam, +20 F minimum storage and use temperature. Hydrocarbons and Polar fuels only at 3 percent.

FOMTEC AFFF-ARC 1x3 ULTRA, nominal 3 percent Alcohol Resistant Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels at 1 percent. Polar solvent fuels at 3 percent.

FOMTEC AFFF-ARC 3x3 ULTRA, nominal 3 percent Alcohol Resistant Aqueous Film Forming Foam, +20 F minimum storage and use temperature. Hydrocarbons and Polar fuels only at 3 percent.

FOMTEC AFFF-ARC 3x6 ULTRA, Alcohol Resistant Aqueous Film Forming Foam, +20 F minimum storage and use temperature.

Hydrocarbons fuels only at 3 percent. Polar fuels only at 6 percent.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number EX6015
Report Reference EX6015-20051207
Date 2021-June-22

Foam liquid concentrates as follows:

Fomtec FFFP 3% Ultra, nominal 3 percent Film Forming Fluoroprotein Foam +20 F minimum storage and use temperature. Hydrocarbons fuels only.


FOMTEC AFFF 3% M, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.

Fomtec Enviro USP, nominal 3 percent synthetic foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only. FOR FRESH WATER USE ONLY.

Fomtec Enviro ARK, nominal 3 and 6 percent Alcohol Resistant Synthetic, +35F minimum storage and use temperature. Hydrocarbon and polar fuels at 3 percent and 6 percent. FRESH WATER ONLY AT 3 PERCENT. Not suitable for use with sea water solutions at 3 percent.

Fomtec Enviro ERS, nominal 3 percent synthetic foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only. FOR FRESH WATER USE ONLY.

Fomtec Enviro Ultra, nominal 3 and 6 percent Alcohol Resistant Synthetic, +35F minimum storage and use temperature. Hydrocarbon and polar fuels at 3 percent and 6 percent. FRESH WATER ONLY AT 3 PERCENT. Not suitable for use with sea water solutions at 3 percent.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

